

## *NOTES:*

- 1. STREET NAME SIGN SHALL BE IN CONFORMANCE WITH THE LATEST EDITION OF THE M.U.T.C.D.
- 2. ALL SIGN LETTERING SHALL BE IN UPPERCASE LETTERS AS PROVIDED IN THE STANDARD ALPHABETS FOR HIGHWAY SIGNS AND PAVEMENT MARKINGS.
- 3. REFLECTIVE MATERIALS SHALL BE MOUNTED ON .080 GAUGE FLAT PLATE ALUMINUM NO. 6061-T6.
- 4. REFER TO STANDARD DETAIL DRAWING NO. R-415 (332) FOR MOUNTING AND POLE REQUIREMENTS, UNLESS OTHERWISE SPECIFIED.
- 5. A MINIMUM OF FOUR(4) SIGNS, PLACED BACK—TO—BACK PER STANDARD
  DETAIL DRAWING NO. R—415 (332), FOR EACH STREET IS REQUIRED.
  TWO(2) INSTALLATIONS ARE REQUIRED AT A FOUR—LEG INTERSECTION AND
  ONE(1) INSTALLATION IS REQUIRED AT A THREE—LEG OR LESS INTERSECTION.
- 6. THE SIGN IS TO INCLUDE THE "BLOCK" NUMBER, ROUNDED TO THE NEAREST HUNDREDTH, OF THE CLOSEST ADDRESS TO THE SIGN ON THE STREET.
- CONTACT THE CITY OF RENO'S CORPORATION YARD AT 334-2246 FOR INFORMATION ON THE CITY OF RENO LOGO.

L	NO.	REVISION	DATE	STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION	SECTION RENO
	1	REV. NOTE 5	02/01		
2	2	LETTERING	05/05	CTDEET NIAME CICNI	DRAWING NO. R-401 (332)
				JAKEET NAME SIGN	DATE , PAGE
	APPROV	ED BY: G.S.	07/05		08/00 1702 400